

audio-technica

Infrared Wireless Microphone

CLM7700 SERIES


Light, compact short-type microphone





AT-CLM7700TSX(US)

Dimensions



Туре	Dynamic
Polar pattern	Cardioid
Modulation method	FM frequency modulation
Tone signal	35.7 kHz
Carrier frequency	A channel: 3.20 MHz, B channel: 3.70 MHz
Infrared wavelength	870 ±30 nm
Power supply	2.4 to 3 V DC (when using the dedicated nickel-metal hydride battery or two AA alkaline dry cells)
Continuous use time*	When using the dedicated nickel-metal hydride battery Approx. 10 hours (ECO mode) Approx. 7.5 hours (LO mode) Approx. 4.5 hours (HI mode) When using AA alkaline dry cells Approx. 8 hours (ECO mode) Approx. 5.5 hours (LO mode) Approx. 3 hours (HI mode)
Operating temperature range	5°C to 40°C
Dimensions	56 mm × 223 mm (Head dia. × Full length)
Weight	Approx. 275 g (including dedicated nickel-metal hydride battery)
Accessories	Dedicated nickel-metal hydride battery RB3UTG (1900 mAh) (pre-installed in the product) Channel identification ring : Red, Blue

Infrared Wireless Microphone

AT-CLM7700TX(US) AT-CLM7700TSX(US)

- Power-saving type that has 3 levels of infrared output (ECO/LO/HI) for different room sizes
- With up to 10 hours of continuous use (in ECO mode) optimal for karaoke service
- Channels available for up to 2 microphones in the same room
- High sound quality, dynamic microphone unit
- Microphone unit assembly and grip low-assembly can be quickly exchanged
- Each microphone has two available channels* Channels can be identified by the color of the power indicator lamp. Thin channel identification rings are also supplied.

* This product must be used in combination with an Audio-Technica infrared wireless receiver and battery charger that are sold separately. Visit our web site for information on compatible models. ⇒https://www.audio-technica.co.jp/amz/manual_en/index.html