









仕様	型番	ATND971a	ATND8677a	ATW-DR3120DANHH1 ATW-R5220DANDG1	ATUC-IRCUDAN	ATDM-1012DAN	ATND1061DAN	ESW-R4180DAN	ATSP-30DAN
外観									
Dante モジュール		UltimoX2	UltimoX2	UltimoX2	Brooklyn II	Brooklyn II Brooklyn III	Broadway	Broadway Dante IP Core	UltimoX2
Dante port		1port	1port	1port	2ports Primary / Secondary	2ports Primary / Secondary	2ports Single cable / Split	2ports Single cable / Split	1port
ネットワーク 端子モード		—	—	—	Switched / Redundant/ Split	Switched / Redundant/ Split	Single cable / Split	Single cable / Split	—
同時フロー数		2×2	2×2	2×2	32×32	32×32	16×16	16×16	2×2
レイテンシー		1ms/2ms/5ms	1ms/2ms/5ms	1ms/2ms/5ms	0.25ms/0.5ms/1ms/ 2ms/5ms	0.25ms/0.5ms/1ms/ 2ms/5ms	0.25ms/0.5ms/1ms/ 2ms/5ms	0.25ms/0.5ms/1ms/ 2ms/5ms	1ms/2ms/5ms
Input/Output		1out Output→Mic	1out Output→Mic	2out Output → RX1 ~ 2	10in28out Input → MIC/LINE1 ~ 2, AUX L/R,L1x2,L2x2,L3x2 Output → ActiveMic1 ~ 10, MIC/LINE1 ~ 2,AUX L/R, Return1 ~ 2,Output1 ~ 4, Group0 ~ 3,Floor,L1 ~ 3	16in22out Input → 1 ~ 16 Output → BUS1 ~ 12, DirectOut1 ~ 10	8in8out Input → AEC Ref In,Sum In,Chain In,Mix In Output → CH1 ~ 5,CH6/ AutoMix,AEC Ref Out, Sum Out	8out Output → RX1 ~ 7,RX8 / MIX	2in → Main/Ext
ネットワーク インターフェース		100Mbit	100Mbit	1Gbit	1Gbit	1Gbit	1Gbit	1Gbit	100Mbit
電源		PoE IEEE802.3af (Class 0), IEEE802.at準拠	PoE IEEE802.3af (Class 0), IEEE802.at準拠	AC100V	AC100V	AC100V	PoE IEEE802.3af (Class 0), IEEE802.at準拠	PoE IEEE802.3af (Class 0), IEEE802.at準拠	PoE IEEE802.3af (Class 0), IEEE802.at準拠
AES67 mode対応		○	○	○	○	○	○	○	○
Dante Domain Manager対応		○	○	○	○	○	○	○	○
Danteバージョン		4.2.2.3	4.2.2.3	4.2.2.3	4.2.0.28	II 4.2.8.2 III 4.2.10.4	4.2.6.4	4.2.6.4	4.2.9.10